

500 KW DRIVE



EXTREME POWER,
ENGINEERED TO FIT YOUR WORLD

315 kW to 500 kW | Up to 865 A

380 to 480 VAC ($\pm 10\%$)
500 to 575 VAC ($\pm 10\%$)
500 to 690 VAC ($\pm 10\%$)

500 kW Drive Highlights

- A single installer can handle wiring and connection using comprehensive accessories
- Under 30 minutes for one engineer to replace the drive using service accessories
- During service, factory-tested sub-assemblies can be exchanged on site without returning the drive to base
- Wider front face design and lower centre of gravity provide greater physical stability and safety during installation
- Always smaller than an existing drive when retrofitting, so will always fit space available
- Fixed lifting points on the chassis (no additional brackets required) for safe handling
- No additional chokes are required for the vast majority of applications






500 KW DRIVE VARIANTS

Available with a control stage to suit any application:

- Industrial automation systems based upon induction or servo motors, where control dynamics are key
- HVAC/R systems where dedicated drive features provide overall system control
- 500 kW supports the latest high-efficiency motors to maximise return on investment and minimise impact on the environment

Select from:

Unidrive M700, M701, M702, Pump Drive F600 or HVAC Drive H300

M700		Ethernet	<ul style="list-style-type: none"> • Onboard real-time multi-protocol Ethernet • 1 x Safe Torque Off (STO) certified to SIL3/PLe • Analogue and digital I/O
M701		Unidrive SP replacement	<p>Designed to match Control Techniques' highly popular Unidrive SP feature-set.</p> <ul style="list-style-type: none"> • Modbus RTU over RS485 communications • 1 x STO certified to SIL3/PLe • Analogue and digital I/O
M702		Safety enhanced	<ul style="list-style-type: none"> • Onboard real-time multi-protocol Ethernet • 2 x STO certified to SIL3/ PLe • Digital I/O - If Analogue I/O is required, this can be provided by an SI-I/O option module
F600		Pumping	<ul style="list-style-type: none"> • Dedicated, specialist pump drive delivers precise, dependable flow control • Comprehensive pump protection and energy saving features significantly reduce total cost of ownership
H300		HVAC	<ul style="list-style-type: none"> • Dedicated, specialist HVAC drive optimised for fan and compressor applications • Modbus RTU and BACnet MS/TP communications provide seamless integration with Building Automation Systems

Please refer to the individual product data sheets for key information

Output frequency


500 kW drives have a maximum output frequency of 599Hz and are, therefore, not subject to special export controls.

DIMENSIONS

Width	Height	Depth
295mm	1750mm	526mm

Documentation & Downloads

Product documentation and PC tools available for download from:
www.controltechniques.com/support




DRIVE RATINGS AND ORDERING INFORMATION

	Order Code Start	No Overload			Normal Duty (110% Overload)				Heavy Duty (140% Overload)			
		Max. Cont. Output Current	Motor Shaft Power		Max Cont. Current	Peak Current	Motor Shaft Power		Max Cont. Output Current	Peak Current	Motor Shaft Power	
		A	kW	hp	A	A	kW	hp	A	A	kW	hp
400 V	M000-12404800	635	315	500	608	668	315	500	480	672	250	400
	M000-12405660	689	355	550	660	726	355	550	566	792	315	450
	M000-12406600	788	450	650	755	831	400	650	660	924	355	550
	M000-12407200	903	500	700	865	952	500	700	720	1008	400	600
575 V	M000-12503150	375	250	350	360	396	250	350	315	441	250	350
	M000-12503600	426	300	400	410	451	300	400	360	504	250	350
	M000-12504100	479	330	450	460	506	330	450	410	574	300	400
	M000-12504600	530	370	500	510	561	370	500	460	644	330	450
690 V	M000-12603150	375	355	550	360	396	355	550	315	441	280	500
	M000-12603600	426	400	600	410	451	400	600	360	504	355	550
	M000-12604100	479	450	650	460	506	450	650	410	574	400	600
	M000-12604600	530	500	700	510	561	500	700	460	644	450	650

NOTES: Internal 125 kW brake chopper included as standard
 Continuous currents at 2 kHz switching frequency
 40°C ambient

Order Code Finish Format
 ...TU0100AB100 AC to AC
 ...DU0100AB100 DC to AC



© 2021 Nidec Control Techniques Limited. The information contained in this brochure is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as Nidec Control Techniques Ltd have an ongoing process of development and reserve the right to change the specification of their products without notice.

Nidec Control Techniques Limited. Registered Office: The Gro, Newtown, Powys SY16 3BE. Registered in England and Wales. Company Reg. No. 01236886